

Systems Inc. Flexible Screw Application Data Sheet

Need Help? Call the experts at 814-899-2103.

	CUST	OMER CONT	ACT DE	TAILS						
			Name	:						
Address:										
City:										
State: Zip:										
MATERIAL CHARACTERISTICS – Please check all types that apply										
Material Name:										
Flowa	bility	Abrasive	ness		Othe	r Chai	racteristics			
Liquid	d Like	☐ Not Abr	asive	☐ Dusty			☐ Interlocks			
☐ Free I	Flowing	☐ Mildly		☐ Flam	 □ Flammable		☐ Very Light			
☐ Slight	:ly	Abrasive		☐ Stick	☐ Sticky		☐ Breaks Down			
Gummy		☐ Modera	te	☐ Corre	osive	j	Under Pressure			
□ Very	Gummy	□ Very Ab	rasive	☐ Pack	s un	der	☐ Hygroscopic			
☐ Harde	ens			Pressur	essure		☐ Builds Static			
☐ Aerat	es									
☐ Bridges										
			•							
,										
		<u> </u>				F				
						•				
Please provide any operational information not listed above: UTILITIES – Please complete all known information.										
UTILITI	ES – Pleas	se complete	all kno	wn infor						
UTILITI	I ES – Plea s 160 VAC, 3	se complete 3 PH, 60 Hz	all kno Electr	wn infor ical		NEMA	4/12 (STD.)			
UTILITI	ES – Plea 460 VAC, 3 230 VAC, 3	se complete	all kno	wn infor ical	1 🗆	NEMA NEMA	4X SS			
UTILITI	ES – Pleas 460 VAC, 3 230 VAC, 3 er:	se complete 3 PH, 60 Hz 3 PH, 60 Hz	all kno Electr	wn infor ical	1 🗆	NEMA	4X SS			
UTILITI	ES – Pleas 460 VAC, 3 230 VAC, 3 er: General Pi	se complete 3 PH, 60 Hz 3 PH, 60 Hz	all kno Electr Enclos	wn infor ical sure:	l 🗆 l	NEMA NEMA er:	4X SS			
	Floward Liquid Slight Gummy Aerat Bridge materiar Pharge: epose:	Flowability Flowability Liquid Like Free Flowing Slightly Gummy Very Gummy Hardens Aerates Bridges material specifics material specifics ONAL INFORMATION harge: lbs./ epose: deg	Flowability Abrasives Liquid Like	Name Title: E-mail Zip:	Title: E-mail:	Name: Title: E-mail: Phone: EFIAL CHARACTERISTICS – Please check all types to Dusty Dusty Free Flowing Mildly Flammab Slightly Abrasive Sticky Gummy Moderate Corrosive Very Gummy Very Abrasive Packs under Pressure Press	Name: Title: E-mail: Phone: Phone:			

Erie Technical Systems Inc. Phone: 814-899-2103



Systems Inc. Flexible Screw Application Data Sheet

Need Help? Call the experts at 814-899-2103.

FlexMAX® Flexible Screw Conveyor Features:

Inlet Hoper Size:	☐ 4 cu. ft.☐ 8 cu. ft.☐ 12 cu. ft.☐ Other:	Optional Flow Aids:	 □ Rotary Electric Vibrator □ Pneumatic Vibrator (5-21 SCFM) □ Fluidization Pads (4-8 SCFM) □ Agitator (8 cu. ft. hopper min.)
Optional Std. Features:	 ☐ Hinged Lid ☐ Bag Break Dust Hood ☐ Bag Slitter Shelf ☐ Low Level Switch ☐ Portable Base (Steel) 	Controls:	☐ No Controls☐ Variable Speed Control☐ Remote Start/Stop
	☐ Portable Base (304 SS)☐ Tilting Portable Base☐ 304 SS Casing	Optional Supporting Equipment:	□ Bulk Bag Unloader□ Dust Collector□ Bag Filler
Please provide	e any operational information	on not listed a	above:



Submit Completed form to: info@erietechnicalsystems.com
NOTE: If save button does not work in your browser, use the standard SAVE button to save a local copy and submit.